

Model DX-3210ST

VERTEX[®]
Short Throw DLP Projector



Powerful, Compact, Reliable

High Brightness of 4,200 ANSI Lumens.

Native XGA resolution and support UXGA resolution

High Contrast 10000 : 1

8,000 Hrs lamp life (Eco Mode)

VERTEX®

Short Throw DLP Projector

Model DX-3210ST



Other Features

- DLPLink for 3D Projection
- Auto Rotate when mounted in ceiling
- Auto Power-Off when no signal input
- Auto Synch.
- Auto Detection of Input Source
- Blank Screen with one hotkey
- Password Protection
- Image Freezing, Zoom & Panning

Display Technology	DLP Technology
Display Panel Type	1 x 0.55" DMD
Brightness (Ansi Lumens)	4,200
Native Resolution	XGA (1024 x 768)
Contrast Ratio	10000:1
Projection Lens	F : 2.6-2.8 , f=6.96 mm. (10X Digital Zoom)
Uniformity	85%
Throw Ratio	81.5"@1m
Throw Distance	20"-350"
Aspect Ratio	4:3(Native)/16:9(Compatible)
Keystone	V +/- 40 (Auto+Manual)
Input	HDMI x 2 VGA x 2 Audio In (Mini Jack) x 1 Audio In (L/R) x 1 Component x 1(Share with VGA port) Video x 1 S-Video x 1
Output	VGA x 1 Audio Out (Mini jack) x 1
Control	RS-232 x 1 , RJ-45 x 1 USB-B x 1
PC Compatibility	VGA SVGA XGA SXGA WXGA UXGA Mac
Video Compatibility	Auto,PAL,SECAM,NTSC 4.43,PAL-M,PAL-N 480i,480p,576i,576p,720p,1035i and 1080i
Lamp	215W
Lamp Life	6,000 Hrs(Norm)/8,000 Hrs(Eco)
Remote Control	Yes
H~Synch Range	15~100 KHz
V~Synch Range	48~125 Hz
Standby Power	<1W
Power Consumption	280W
Power Supply	100V - 240V @ 50-60Hz
Operating Temp.	5 °C~40 °C
Store Temp.	-10 °C~65 °C
OSD Languages	19 languages Include English and Thai
Speaker	10 W
Standard Accessories	Remote Control with Battery, User Manual, VGA Cable, Power Cable
Weight	3.5 Kg

