

Model LX-3310ST

VERTEX[®]
Short Throw LCD Projector



Powerful, Compact, Reliable

High Brightness of 4,100 ANSI Lumens.

Native XGA resolution and support UXGA resolution

High Contrast 10000 : 1

10,000 Hrs lamp life (Super Eco Mode)

Off to Go with high-speed power off feature





Other Features

- Security Bar
- Kensington Lock
- Password Protections
- Control Panel Lock
- Digital Zoom
- Image Freeze
- Audio Muting (Muting)
- Picture Muting (Blank)
- Direct Power On/Off
- Off to Go with high-speed power off
- Picture Mode : 6 Modes

Display Technology	Liquid Crystal Display
Display Panel Type	3 x 0.63" Poly Silicon TFT
Brightness (Ansi Lumens)	4,100
Native Resolution	XGA (1024 x 768)
Contrast Ratio	10000:1
Projection Lens	F : 1.8 , f=6.08mm. (Digital Zoom)
Uniformity	85%
Throw Ratio	81.5"@1m
Throw Distance	20"-350"
Aspect Ratio	4:3(Native)/16:9(Compatible)
Keystone	V +/- 40 (Auto+Manual)
Input	HDMI x 1 VGA x 1 Audio In (Mini Jack) x 1 Audio In (L/R) x 2 Component (Share with VGA port) Video x 1, S-Video (Share with VGA port)
Output	VGA x 1 Audio Out (Mini jack) x 1
Control	RS-232 x1 USB-B x 1
PC Compatibility	VGA SVGA XGA SXGA WXGA UXGA Mac
Video Compatibility	Auto,PAL,SECAM,NTSC 4.43,PAL-M,PAL-N 480i,480p,576i,576p,720p,1035i and 1080i
Lamp	215W
Lamp Life	6,000 Hrs(Norm)/8,000 Hrs(Eco)/10,000 Hrs(Super Eco)
Remote Control	Yes
H~Synch Range	15~100 KHz
V~Synch Range	48~125 Hz
Standby Power	<1W
Power Consumption	280W
Power Supply	100V – 240V @ 50-60Hz
Operating Temp.	5 ° C~40 ° C
Store Temp.	-10 ° C~65°C
OSD Languages	26 languages Include English and Thai
Speaker	10 W
Standard Accessories	Remote Control with Battery, User Manual, VGA PoCable, w Cableer
Weight	3.8 Kg

